UNITED STATES DEPARTMENT OF COMMERCE • MAURICE H. STANS, Secretary
NATIONAL BUREAU OF STANDARDS • Lewis M. Branscomb, Director

HANDBOOK H28 (1969) SCREW-THREAD STANDARDS FOR FEDERAL SERVICES

PART I

UNIFIED UNJ UNIFIED MINIATURE SCREW THREADS



NBS Handbook H28 (1969)

Superseding H28 (1957) Part I and that applicable to Part I in the 1963 Supplement to H28

Nat. Bur. Stand. (U.S.), Handb. 28, 237 pages (Dec. 1969) CODEN: NBSHA

Issued March 1970

		Reference	
Designation	Thread series	United States of America (USA) Standard	H28
ACME-CACME-G	Acme threads, centralising Acme threads, general purpose (See also "Stub Acme")	B1.5 B1.5	Part III Part III
AMOANPT	Microscope Objective threads	B1.11 MIL-F	Part III -7105
F-PTF		B2.2	Part II Part III
N BUTT N, NC, NF, NEF	Buttress threads	B1.9	Part II1
NGO (b) NGS NGT	Gas straight threads Gas taper threads	B57.1	Part II
NH, NPSH		B2.4	Part II Part II
ANPT NPSC NPSL NPSM NPT NPTR	Straight pipe threads in pipe couplings Straight pipe threads for loose-fitting mechanical joints with locknuts Straight pipe threads for free-fitting mechanical joints for fixtures Taper pipe threads for general use	MIL-F B2.1	P-7105
F-PTF NPSF NPSI NPTF PTF-SAE, SHORT PTF-SPL, SHORT PTF-SPL, STARA SHORT SPL-PTF	Dryseal fuel internal straight pipe threads Dryseal intermediate internal straight pipe threads Dryseal taper pipe threads Dryseal SAE short taper pipe threads	B2.2	Part II
NR, NSSGT		B57.1	Part II
SPL-PTF	See under "Dryseal pipe threads"		
STUB ACME	Surveying instrument mounting threads	B1.8	Part III Part III
UN series UNJ series UNM	See table 1.8a (0.06 in. (1.5 mm) and larger) See table 1.8a (0.06 in. (1.5 mm) and larger)	B1.10	Section 5

^a Methods of designating multiple threads are shown in USA B1.5, Acme screw threads, and Part III of Handbook H28.
^b All threads, except NGO, are right hand unless otherwise designated. For NGO threads, designations "RH" or "LH" are required.

Table 1.8a. Designations for UN, UNJ, N, NR thread series

Basic thread series	External thread root	Constant pitch	Coarse	Fine	Extra fine	Special diameters, pitches, or lengths of engagement	Reference	
							United States of America (USA) Standard	H2 8
UN	With optional radius root on external thread.	UN	UNC	UNF	UNEF	UNS	B1.1 B1.1	Section 2 Section 3
UNJ	With 0.15011p to 0.18042p mandatory radius root on external thread.	UNJ	UNJC	UNJF	UNJEF	UNJS		Section 4
N ⁸		N	NC	NF	NEF	NS		Appendix A1
NR		NR					MIL-B-7838	

^a This series superseded by UN series.